



Key Features

- Durable design is weather resistant.
- Comfortable, ergonomic design permits effortless, one-handed operation.
- The perfect selection of buttons for basic audio/video control.
- Four source and eight general purpose buttons are fully assignable/programmable.
- Easy to use Windows® based software for programming and customization.
- Transmits commands using RF for operation through walls, cabinets, etc.
- Completely customizable and programmable.
- Tactile feedback on all buttons.
- Includes mounting clip for attaching to walls or other surfaces.
- Optional 'Voltage' and 'Video' sensing modules to monitor power status of equipment when used with certain RTI processors.
- Optional interface for RS-232 controlled equipment when used with certain RTI processors.
- Non-volatile Flash memory stores your system configuration even when power is not present.
- Field upgradable firmware.
- USB Programming.
- Includes four (4) AAA alkaline batteries.

U1 Weather Resistant Controller

The U1 Remote Control provides a rugged interface option for communicating with RTI remote control processors.

The U1 was designed for reliable wireless control of audio/video systems from environments which are too harsh for normal remote controls. It is completely sealed, making it weather resistant. Whether indoors or out, the U1 is a perfect companion for hot tubs, pools, bathrooms, and decks.

Description

The U1 Remote Control is programmed using the same intuitive Integration Designer® Software that RTI has become famous for. The U1 allows the basic functions of other factory remotes to be combined into a simple one-handed user interface for command of any audio/video system.

The U1 is designed to be used with RTI remote control processors, making it more than just another remote control - it's an expandable control system. When used with the available RTI accessory devices, the U1 is capable of power sensing for reliable operation, and RS-232 communications for advanced control.

Call 952-253-3100

www.rticorp.com



It's Under Control®

Specifications

Power.....	4 AAA alkaline batteries
Radio Frequency Control Range.....	Up to 100 feet (30.5 meters)
Radio Frequency Carrier.....	433 MHz
Operating Temperature.....	+32°F to +122°F (0°C to +50°C)
Operating Humidity.....	5% to 100%
Standby Time with new batteries.....	1000 Days
Total System Memory.....	16K Bytes Flash (non-volatile) memory
Device Capability.....	Four device pages (sources)
Macro Capability.....	Macro capability on every button
Communications.....	USB programming port
Dimensions (L x W x D).....	5.9 in (150mm) x 2.3 in (59mm) x 1.2 in (30mm)
Enclosure.....	High-impact molded ABS plastic with textured finish
Weight.....	5.5 oz. (156g) with batteries
Warranty.....	One Year (Parts & Labor)

All specifications subject to change without notice




Accessories

RP-1	Remote Control Processor
ZRP-6	Remote Control Processor
MRP-64	Multi-Room Control Processor
XP-8	Advanced Control Processor
RM-433	RF Receiver
RCM-12	Relay Control Module
ECB-5	IR Emitter Connecting Block
CM-232	RS-232 Communication Module
VPS-1	Voltage Power Sensor
SPS-1	Video Sync Power Sensor



Other RTI Products

T1-B	Universal System Controller
M2	Universal System Controller
T2-B	Universal System Controller
T2-Cs	Universal System Controller
T2-C	Universal System Controller
T3-V	Universal System Controller
T4	Universal System Controller
U2	Weather Resistant Controller
RKM-1	In-Wall Multi-Room Audio Keypad
RK1	In-Wall Keypad Controller
RK2	In-Wall Touchscreen Controller
RK3	In-Wall Touchscreen Controller
K4	In-Wall Touchscreen Controller
ZM-24	2.4GHz Transceiver Module
IR-PRO	Infrared Capture System



Integration Designer® Programming Software