XP-8



Key Features

- Powerful 32-bit, 200MHz XScale® processor.
- 32MByte of non-volatile Flash memory.
- Front panel controls/display (11 Buttons for front panel control).
- Two USB ports.
- Eight multi-purpose I/O ports.
- · Eight programmable relay outputs.
- Eight two-way RS-232 ports.
- · Eight sense inputs.
- \bullet I/O ports are compatible with industry standard IR emitters, blasters, and repeater systems.
- All output ports incorporate both short-circuit and overload protection.
- · Variable IR output on all ports.
- I/O ports support all optional RTI power sensing and communications modules.
- Programmed using the Integration Designer® Software.
- Non-volatile Flash memory stores your system configuration even when power is not present.
- · Field upgradable firmware.
- USB and Ethernet programming.
- Input for connection of both 433MHz and 2.4GHz Zigbee® RF modules.
- RS-485 communications port for future expansion.
- · Astronomical clock built in.
- Rack mountable or free standing.

Call 952-253-3100 www.rticorp.com

XP-8 Advanced Control Processor

The XP-8 is a high-end remote control processor for automating the operation of electronic systems in homes and office buildings. The combination of a blazing fast MPU, real time/multitasking operating system, and tremendous expandability make the XP-8 the perfect solution for large-scale and complex projects.

Description

The XP-8 provides an unmatched value with it's powerful features and ease of programmability, offering an advanced level of control typically only found on more expensive processors. The XP-8 offers an abundance of advanced control interface options such as two-way RS-232, routable IR, relay control and Ethernet, ideal for large-scale and more advanced projects. Additionally, the XP-8 incorporates an astronomical clock, allowing for time based events or commands.

Like other RTI processors, the XP-8 has been designed to interface seamlessly with all RTI remote controls and touchpanels. The XP-8 has eight multi-purpose I/O ports that accept standard IR emitters and repeater systems with variable IR output. These multi-purpose ports also support optional video/voltage sensing modules, allowing for expanded integration capabilities. The XP-8 also features eight programmable relay input/ outputs, eight sense inputs, eight two-way RS-232 ports and an RS-485 jack for expansion purposes. Unlike simple IR-to-RF converters, the XP-8 creates central storage for all system commands. With these interface and control options, the XP-8 provides an almost unlimited arsenal of control capabilities.



Specifications

Power Supply	+12VDC, 1A	
Multi-Purpose Output Ports	Eight custom 3.5mm 4-conductor jacks	
Designed for RTI modules as well as industry-standard IR emitters.		
IR Output Drive	100mA maximum (per port, adjustable)	
	200mA maximum (high IR output port)	
Infrared Frequency Transmission Range	15kHz - 460kHz	
Infrared Input Compatible with industry-standard repeaters and receivers		
Relays Eigh	nt, 3 Amps @ 30 VDC or 12V/100mA Trigger	
Sense Inputs	Eight, Analog/Digital/Closure	
RS-232 Ports	Eight, RJ45 Connections	
Ethernet Port	10/100Base-T	
USB Ports	Two Host, 1 Programming	
Expansion Port	RS-485 / IR / PWR	
Memory Expansion	SD/MM Card Slot	
Display	High-contrast STN LCD	
Display Size (H x W)	0.7 in x 2.8 in (18mm x 60mm)	
Backlights	Blue LED (Display/Keypad)	
Mounting	Rack-mount or free standing	
<i>Dimensions (W x H x D)</i> 17 in (432mm) x 1.7 in (43mm) x 6.4 in (162mm)		
Weight	4 lb. (1814g)	
Warranty	One Year (Parts & Labor)	

All specifications subject to change without notice



Front view - cover removed



Rear view

5775 12th Avenue East, Suite 180, Shakopee, MN 55379 PH: (952) 253-3100 • Website: www.rticorp.com

Accessories

RM-433	RF Receiver
ZM-24	2.4GHz Zigbee [®] Transceiver Module
PCM-8	Port Control Module
CB-8	Touchpanel Connecting Block
RCM-12	Relay Control Module
ECB-5	IR Emitter Connecting Block
vIRsa Mouse	IR Emitter
CM-232	RS-232 Communication Module
VPS-1	Voltage Power Sensor
SPS-1	Video Sync Power Sensor



Other RTI Products

Virtual Panel	PC Control Application
RTiPanel	Mobile Device Control Application
T1-B	Universal System Controller
M2	Universal System Controller
Т2-В	Universal System Controller
T2-Cs	Universal System Controller
T2-C+	Universal System Controller
T3-V+	Universal System Controller
Т4	Universal System Controller
ST-7	Universal System Controller
U1	Weather Resistant Controller
U2	Weather Resistant Controller
RKM-1	In-Wall Multi-Room Audio Keypad
RK1	In-Wall Keypad Controller
RK2	In-Wall Touchscreen Controller
RK3-V	In-Wall Touchscreen Controller
K4	In-Wall Touchscreen Controller
RK-10	In-Wall Touchscreen Controller
0	



Integration Designer[®] Programming Software

